



# TORF FITTINGS

(THREADED-O-RING, FLANGED)

WorldWide Machining & Welding, Inc. has developed a single bodied TORF (Thread-O-Ring, Flanged) fitting with integral reinforcement.

This new single body design reduces the number of welds required during the manufacturing process. The elimination of the weld between the main body and the weld-o-let reduces manufacturing costs and increases the overall strength of the TORF.

## FIELD APPLICATION

TORF fittings can be used in a variety of applications, such as for purge and equalization during drain-up operations. TORF fittings are fully compatible with TDW T101 drilling machine, thermometer wells, gauge adapters and other probe instrumentation devices.

## FEATURES/SPECIFICATIONS

- Main body machined out of a solid piece of SA350 LF2 CL1 low temp material.
- Aluminum bronze plug.
- Viton o-ring.
- Teflon o-ring backer.
- CGI 304 gasket with an option for 316.
- Raised face blind flange machined out of SA350 LF2 CL1 low temp material.
- B7 studs and nuts with an option for L7.
- Stamped with size, rating/class, material grade and heat number.
- Material test reports provided for all fittings supplied.

## PROCUREMENT

Price and lead time quotes available upon request.



## MODELS

1.5"	ANSI	150
1.5"	ANSI	600
2.0"	ANSI	150
2.0"	ANSI	300
2.0"	ANSI	600
2.0"	ANSI	900

Custom sizes available upon request  
200 unit on-hand inventory maintained for the following: 2" 150# TORFs and 2" 600# TORFs.

*Please reference the order drawings to designate fitting size, class rating and additional specifications.*

